



Features & Benefits

- Tamperproof option
- Bi-metallic switch mechanism for reliability

Technical Overview

The ST-TY series of wall mounting space thermostats are suitable for heating and/or cooling and frost protection applications.

Specification

Ambient range	50°C max
Contact configuration	SPST
Dimensions	88 x 86 x 38mm
Housing material	ABS
Operating voltage	230Vc 50-60Hz
Sensor system	Dual diaphragm sensing element
Switching current	230Vac @ 10(3)A
Switching differential	1°C
Weight	190g

Technical Specification

Temperature range	5° to 30°C
Ambient range	50°C max
Weight	190g
Dimensions	88 x 86 x 38mm
Housing material	ABS
Operating voltage	230Vc 50-60Hz

Related Product Codes

ST-RSTAT1	Thermostat Space with Dial 10-30 deg C
ST-RSTATT	Thermostat Space Tamperproof 5-30 deg C
ST-TY92-C1	Thermostat Space Mount Heating 5-35 degC
ST-TY92-C1F	Thermostat Space Mount Frost -5-15 degC
ST-TY92-C3	Thermostat Space Mount Htg or Clg 5-35 degC
ST-TY92-C3T	Thermostat Space Htg or Clg Tamperproof 5-35 degC