

Silhouette® 100

Axial Bathroom/ Toilet Fans



Features & Benefits

- 17mm stylish ultra low profile grille
- Downstream airflow guide vanes for improved pressure development
- Designed for vertical or horizontal application
- Indication light
- Fan IPX4 rated
- Suitable for wall, ceiling, panel and window mounting
- Meets current Building Regulations Approved Document F

Slimline Bathroom Ventilation

With a slim profile of only 17mm, Silhouette blends in with the wall surface to provide an unobtrusive installation. Silhouette has a FID performance of 21 l/s. Silhouette can be ceiling/panel mounted and connected to an appropriate duct run to the outside.



17mm actual profile



Back draught prevention vanes
fitted on discharge

Models

Silhouette 100B

Single speed 100mm bathroom/toilet fan with indication light and back draught shutter.

Stock Ref

454055

Silhouette 100T

(Timer)

Single speed 100mm bathroom/toilet fan with integral adjustable electronic overrun timer (5-30 minutes), indication light and back draught shutter.

Stock Ref

454056

Silhouette 100H

(Humidity)

Single speed 100mm bathroom/toilet fan with integral adjustable auto humidity sensor from 60-90% RH, indication light and back draught shutter.

Stock Ref

454057

Silhouette 100TM

(PIR/Timer)

Single speed 100mm bathroom/toilet fan. Integral PIR operated model, (presence detector) with adjustable electronic overrun timer (5-30 minutes) indication light and back draught shutter.

Stock Ref


454058

Dimensions (mm)


A	BØ	C	D	E	F
160	100	80	97	200	32

Weight 0.6kg

Panel



Wall



Fixing hole diameter 117mmØ

Wall Kit

Stock Ref

254102 (White)

254100 (Brown)

Window kit

Stock ref

442947

Performance

Extract Performance - FID

Sound dB(A)

Model	m³/h	l/s	Watts	@ 3m
Silhouette 100B/T/H/TM	75	21	14	38